



Test Report : DI06W8-15

6W 1"x1" Package 8:1 Ultra-Wide Input DC-DC Regulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

Other Test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDITC
1	VOLTAGE ACCURACY	-1% ~ +1 %	I/P:24VDC O/P:FULL LOAD Ta:25°C	-0.19% -0.17%	P
2	RIPPLE & NOISE	100 mVp-p	I/P:24VDC O/P:FULL LOAD Ta:25°C	35 mV 35 mV	P
3	LINE REGULATION	-0.2% ~ +0.2%	I/P:9VDC~75VDC O/P:FULL LOAD Ta:25°C	+0.01% ~ +0.00% +0.01% ~ +0.00%	P
4	LOAD REGULATION	-0.5% ~ +0.5%	I/P:24VDC O/P: 0% LOAD~FULL LOAD Ta:25°C	+0.00% ~ +0.01% -0.01% ~ +0.00%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDITC
1	INPUT VOLTAGE RANGE	9 VDC ~75 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.07 VDC ~ 75 VDC	P
2.	EFFICIENCY	84.5%	I/P:24VDC O/P:FULL LOAD Ta:25°C	84.63%	P
3	DC CURRENT	309 mA / FULL LOAD 11 mA / NO LOAD	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	293 mA / FULL LOAD 9.3 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDITC
1	SHORT PROTECTION	CONTINUOUS	I/P:75DC O/P:FULL LOAD Ta:25°C	AUTOMATIC RECOVERY	P
2	OVER LOAD PROTECTION	110~230%	I/P:24VDC O/P:TESTING Ta:25°C	181.0% HICCUP MODE AUTO-RECOVER	P
3.	UNDER VOLTAGE LOCKOUT	START-UP 8.8V SHUTDOWN VOLTAGE 8.5V	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.49 VDC 8.07VDC	P

■ AFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	WITHSTAND VOLTAGE	I/P-O/P:3.0K VDC/min	I/P-O/P:3.0K VDC/min Ta:25℃	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25℃	I/P-O/P>100MΩ NO DAMAGE	P

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT												
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=25℃ 2. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=71℃ 3. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:50% LOAD Ta=85℃ 4. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:20% LOAD Ta=90℃ <table><tr><th>NO</th><th>Position</th><th>1</th><th>2</th><th>3</th><th>4</th></tr><tr><td>1</td><td>CASE</td><td>44.8℃</td><td>89.1℃</td><td>96.7℃</td><td>100.0℃</td></tr></table>			NO	Position	1	2	3	4	1	CASE	44.8℃	89.1℃	96.7℃	100.0℃	P
NO	Position	1	2	3	4												
1	CASE	44.8℃	89.1℃	96.7℃	100.0℃												
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:24VDC O/P: FULL LOAD Ta= -40℃	TEST : OK	P												

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	MTBF	MIL-HDBK-217F,GB,25℃ TOTAL FAILURE RATE : 2.89246 M.T.B.F : 345,726.83 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG